# **FILANOALGAE**

#### ALGAE REMOVER AND ANTI-MOULD DETERGENT





- TERRACOTTA
- **OUARRY TILES**
- GLAZED

  CERAMIC TILES
- POLISHED MARBLE
  AND AGGLOMERATES
- UNPOLISHED MARBLE
  AND AGGLOMERATES
- PORCELAIN
  STONEWARE
- **CONCRETE**
- **WALLS**







### **WHAT IT'S FOR**

- Eliminates algae, moss and lichen from external wall and floor surfaces.
- When used after FILASMUFFY, it provides protection against mould formation.

## **ADVANTAGES**

- Easy to use spray applicator.
- Perfect for both vertical and horizontal surfaces.
- Long lasting action.
- Perfect for many different surface types: roofs, walls, pavings, terracotta stairs, quarry tiles, brick veneers, natural stone and concrete.
- Guaranteed results on external surfaces: just spray then leave to act for a few days.
- No need to rinse.

# **HOW IT'S USED**

**Ready to use**: no dilution required **Application**:

- Spray the product onto the surface to be cleaned. Use an airless applicator for larger areas. The product can also be applied using a clean paintbrush. FILANOALGAE will start work immediately, gradually eliminating the green deposits on the surface.
- For perfect results it is necessary to wait 2-3 days, depending on the amount of growth to be removed.
- 3. Once the surface is clean it can be rinsed with water or left for the first rainfall. Any residue of the product will penetrate the material and continue to act, preventing further build-up of undesired growth.

# Caution:

After cleaning it is advisable to apply a waterproofing agent: FILAES82, HYDROREP or FILAHP98.

# DILUTION AND COVERAGE

With one litre:

10/20 m<sup>2</sup>

"Coverage rates are approximate and refer to a single coat of the product"

## Packaging

500 ml bottles with spray trigger in box of 12. 5 liter flasks in box of 4.

#### PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- The product is harmful to plants and vegetation. When rinsing, ensure that the run-off does not come into contact with these

#### TEMPERATURE

Storage temperature: between 5° C and 30° C. Must be applied to material at temperatures between 5° and 30° C.

#### CONTAINS

Cationic surfactant < 5 %

#### **LABELLING**

No risk or safety labels or warnings are required since the product is not classified as hazardous under current regulations.

G TECHNICA

TECHNICAL INFORMATION

Appearance: transparent colourless liquid Odour: slight characteristic odour Density: 1,000 kg/litre

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.

DO/LB 14 REV. 00 - 30/05/2012

